

**SHIELDTM**
LUBRICANTS**TECHNICAL DATA SHEET**

ATF Heavy Duty Synthetic MV

Product Code: SCATFMV - Revision: 20181123

Product Description

Formulated from premium synthetic base stocks and an additive package designed to offer outstanding oxidation stability and anti-wear characteristics. A product that demonstrates excellent frictional stability, EP characteristics, temperature fluidity and resistance to high temperatures encountered during severe operating conditions.

Benefits

- Constant frictional performance.
- Excellent oxidation stability.
- High temperature operation stability.
- Outstanding wear protection and component life.
- Low temperature fluidity.
- Seal compatibility.
- Smooth operation of power transmission and power steering systems.

Applications

Recommended for automatic transmissions and power steering units in cars, vans, trucks, buses, agricultural and industrial machines where the following specifications are required.

Please contact your local sales advisor for more information.

Typical Test Data

Density @ 15°C	-	0.876
Flash Point (°C)	-	>180
Kinematic Viscosity @ 100°C (cSt)	-	7.8
Kinematic Viscosity @ 40°C (cSt)	-	34
Pour Point (°C)	-	<-40
Viscosity Index	-	208

Product Profile

Allison	C4, TES295
Chrysler	HF-2
Ford	Mercon V
GM	Dexron IIIH
JASO	1A
MAN	339
MB	236.9
Volvo	97341
ZF-TE-ML	14C