

**SHIELD<sup>TM</sup>**  
**LUBRICANTS****TECHNICAL DATA SHEET**

## CVT Fluid (Red)

Product Code: SCCVT - Revision: 2019041526

### Product Description

CVT Fluid is formulated from synthetic base stocks and advanced additives that work synergistically to offer high levels of anti-wear, anti-foam and anti-oxidant protection. Specifically designed for use with the new generation of continuous variable transmissions systems that are belt or chain driven. The lubricity and oxidation resistance of CVT Fluid provides long drain periods and less downtime without the loss of the fresh oil feel.

### Benefits

- Superior anti-shudder.
- Extended drain periods.
- Effective foam control.
- Superior wear protection.
- Excellent thermal protection.

### Applications

Suitable for use with a wide variety of Continuous Variable Transmission systems.

Not for use in any other type of transmission. Not suitable in Honda CVT with starting clutch nor some Hybrid systems.

### Typical Test Data

Density @ 15°C	-	0.84
Flash Point (°C)	-	<190
Kinematic Viscosity @ 40°C (cSt)	-	38
Kinematic Viscosity @ 100°C (cSt)	-	7.6
Pour Point (°C)	-	<-40
Viscosity Index	-	170

### Product Profile

Chrysler Jeep	NS-2/CVTF +4
Daihatsu	Ammix CVT
GM	DEX CVT
Honda	HMMF 1 , HCF2
Hyundai	SP-III (CVT Model)
Mazda	JWS 3320
Mini Cooper	EZL799
Mitsubishi	SP-III, CVTF-J1
Nissan	NS-1, 2, 3
Subaru	Lineartronics HT, Chain CVT & CVT 2
Suzuki	CVTF TC , NS-2, CVT Green 1 & 2
Toyota	CVTF TC, CVTF FE
VW/Audi	TL 521 80 (G052 180), TL 521 16 (G052 516)
Chrysler Jeep	NS-2/CVTF +4