

## SHIELD LUBRICANTS 5W30 SEMI SYNTHETIC Product Code: SC5W30SS- Revision: 20200615

## **Product Description**

Viscosity Index

Semi Synthetic 5w-30 ACEA A1/B1 is a fuel-efficient multi-grade engine oil manufactured from a precisely balanced blend of top quality mineral and synthetic base stocks and performance enhancing additives.

The high lubricity of Semi Synthetic 5w-30 ACEA A1/B1 provides lower internal friction for reduced engine wear while the relatively low viscosity improves flow rates and hydraulic tappet performance during cold start and engine idling.

Benefits			Applications	
<ul> <li>Semi-synthetic formulation.</li> <li>Stay in grade properties.</li> <li>Excellent high and low temperature stability.</li> <li>Improved fuel efficiency.</li> <li>Improved oil consumption and emissions.</li> <li>Superior performance to mineral based oils.</li> </ul>			Semi Synthetic 5W-30 ACEA A1/B1 is suitable for normally aspirated and turbocharged engines. Suitable for engines that run on petrol or diesel fuels. Applications include passenger cars and light commercials particularly modern vehicles. Semi Synthetic 5W-30 ACEA A1/B1 is miscible with synthetic and mineral based engine oils.	
Typical Test Data			Product Profile	
Density @ 15°C Flash Point (°C) Kinematic Viscosity cSt @ 100°C Kinematic Viscosity cSt @ 40°C Pour Point (°C) Total Base Number (mg KOH/g)	- - - -	0.857 212 10.5 66.4 -44 9.20	ACEA API Ford ILSAC	A1/B1, A5/B5 SL/CF WSS-M2C913-B GF-3

146