

**SHIELD[™]**
LUBRICANTS**TECHNICAL DATA SHEET****SHIELD LUBRICANTS DSG**

Product Code: SCDSG- Revision: 20181113

Product Description

A synthetic wet dual clutch transmission fluid formulated from highly refined base stocks. It contains an additive package designed to impart the requirements of oxidation stability anti-wear characteristics and frictional stability. Providing a smoother driving experience.

Benefits

- Excellent oxidation and thermal stability.
- High shear resistance.
- Superior friction control allowing smooth gear change.
- Suitable for a wide range of vehicles.
- Pumpability at low temperatures.

Applications

Designed specifically for DSG gearboxes of passenger cars and vans with VW DSG transmissions.

Also suitable for Ford, Audi, Skoda, Nissan with VW DSG transmission.

Not for use in CVT or Dry DCT.

Please contact your local sales advisor for more information.

Typical Test Data

Density @ 15°C	-	0.84
Flash Point (°C)	-	>180
Kinematic Viscosity @ 100°C (cSt)	-	7.0
Kinematic Viscosity @ 40°C (cSt)	-	33.4
Pour Point (°C)	-	<-45
Viscosity Index	-	173

Product Profile

	DCT-1.
Ford WSS	M2C936A
Mitsubishi	MZ320065
Peugeot/	9734.S2
Citroen	
Pentosin	FFL2, FFL3, FFL4
VW TL	45259, 52182
VW	G052 529, G052 182
Volvo	1161838, 1161839